

ITS COW Series
Model COW-15K8/60

Specification Summary: • 15,000lb/6,803kg Capacity GVWR Trailer • Typical 8'x8'x8' (2.4m x 2.4m x 2.5m) Climate Controlled Equipment/Personnel Shelter • 60'/18m HD Locking Pneumatic Mast • Electric or Hydraulic/Surge Brakes • Optional Diesel Generator • 42-Gal /159-liter Fuel Tank



General Specifications (As Shown):

- 15,000lb Capacity GVWR
- ±22' L x 14' W Deployed Footprint
- 7,000lb Capacity Each Outrigger Jacks
- Electric or Hydraulic/Surge Brakes
- Integrated Compressor w/ Mast Controls
- 8x8x8 Shelter OD; 7'4"x7'4"x6'10" ID
- 2-Ton/24,000BTU AC w/ 3kW Heat
- LB & Waveguide Entries; Telco Board
- Optional Sound Attenuated Generator
- Tandem 7,000lb Capacity Axles/Torflex
- 11,000 lb Payload Capacity
- ICC/DOT LED Lighting Package
- Four (4) Telescopic Outriggers
- Payload Access Platform
- Shelter Load (PSF) 40 Snow & 250 Floor
- 100A Service; Set Duplex/Quad Recepts.
- Alarm Terminal Block – Smoke/Fire/Entry
- Optional Auxiliary Fuel Tank
- 16"x6K 8 Hole Wheels/16" LRE Tires
- C8@11.5 Channel Main Frame (50ksi)
- 7,000 lb Capacity Landing Gear
- 1/8" Steel Diamond Plate Deck Panels
- Will-Burt 10-60 HD Locking Mast
- R18 Shelter Walls/Ceiling & R28 Floor
- 100A Manual Transfer Switch (MTS)
- Halo Grounding System; Ground Bars
- Optional Trailer Hitch-Raising Adaptor
- ±22L x 8'0" W x 12'3" H
- 2-5/16" Coupler or 3" Pintle
- Full-Size Spare Tire with Carriage
- Deck-over-Axle Shelter Platform
- 36" Steel Storage Box
- 3'x6' 20 Gauge Steel Entry Door
- Interior/Exterior & Emergency Lighting
- Entry Steps & Shelter Roof Access Ladder
- Optional Coax/Cable Reel and Much More

*ITS COW Series
 Model COW-15K8/60*

