

STILETTO[®] AL

High accuracy electro-mechanical telescoping mast



The Stiletto AL delivers an extremely stable and compact elevation platform for sensors and antennas that require a high degree of pointing accuracy. This high strength alloy electro-mechanical telescoping mast with patented automatic locks does not require guying and safely deploys payloads at any height. The Stiletto AL is a cost-effective elevation platform designed to meet today's stringent program requirements.

High Strength Alloy Construction



Patented Quiet Locks
Designed for Heavy Payloads

Quiet Sealed Direct-Drive System



Integrated Dust Wipers
and Ice-Breakers



STILETTO[®] AL

SPECIFICATIONS

ESSENTIAL FEATURES

Specifications	4 meter	6 meter	8.5 meter	10 meter	15 meter
Extended Height (+4 in. / -0 in.)	13.1 ft. / 4 m	19.6 ft. / 6 m	28 ft. / 8.54 m	32.8 ft. / 10 m	49.2 ft. / 15 m
Nested Height (+1 in. / -0 in.)	50.4 in. / 1.28 m	62.2 in. / 1.58 m	74.02 in. / 1.88 m	82.68 in. / 2.10 m	104.4 in. / 2.65 m
Payload Capacity	400 lb / 181 kg	400 lb / 181 kg	400 lb / 181 kg	400 lb / 181 kg	350 lb / 158 kg
Weight (Including Control and Box Cables)	260 lb / 118 kg	315 lb / 143 kg	353 lb / 160 kg	390 lb / 177 kg	490 lb / 222 kg
Number of Sections	5	6	7	7	8
Tube Diameter	9.85 in. to 6.7 in. / 25 cm to 17 cm	9.85 in. to 5.91 in. / 25 cm to 15 cm	9.85 in. to 5.12 in. / 25 cm to 13 cm	9.85 in. to 5.12 in. / 25 cm to 13 cm	9.85 in. to 4.33 in. / 25 cm to 11 cm
Survival Wind Speed	130 mph / 209 km/h	115 mph / 185 km/h	80 mph / 129 km/h	80 mph / 129 km/h	62 mph / 100 km/h
Deployment Wind Speed	40 mph / 64 km/h	40 mph / 64 km/h	35 mph / 56 km/h	35 mph / 56 km/h	30 mph / 48 km/h
Erection Time with Power	Less than 35 seconds	Less than 60 seconds	Less than 100 seconds	Less than 100 seconds	Less than 150 seconds
Rotation Accuracy (Twist)	+/-1°	+/-1°	+/-1°	+/-1°	+/-1°
Voltage (MIL-STD 1275)	28 VDC	28 VDC	28 VDC	28 VDC	28 VDC
Footprint	17.56 in. x 11.19 in. / 44.6 cm x 28.5 cm	17.56 in. x 11.19 in. / 44.6 cm x 28.5 cm	17.56 in. x 11.19 in. / 44.6 cm x 28.5 cm	17.56 in. x 11.19 in. / 44.6 cm x 28.5 cm	17.56 in. x 11.19 in. / 44.6 cm x 28.5 cm
*Typical Payload Sail Area	17 sqft / 1.58 sqm CD=1.5	12 sqft / 1.11 sqm CD=1.5	11 sqft / 1.02 sqm CD=1.5	11 sqft / 1.02 sqm CD=1.5	8 sqft / 0.74 sqm CD=1.5

- **No guying required, self-supporting mast**
- **Minimal mast twist**
 - Energized keyway guides in accessory-ready collars
- **Low wind deflection**
 - Mast sections are held tight by constricting wear bands
- **Quiet Operation**
 - Direct-drive system powered by environmentally sealed 600 watt DC motor with manual over ride
 - Patented Quiet Locks designed for heavy payloads
- **Reduced maintenance**
 - Clean air filter system prevents dirt from entering mast
 - Integrated dirt / dust wipers and ice-breakers built into collars
- **High strength alloy construction**
- **Integrated PC control**
- **MIL-STD 810G certified**



*Consult factory for larger sail area as payload and wind capacities may be reduced.

CONTACT YOUR SALES REPRESENTATIVE TODAY

The Will-Burt Company, headquartered in Orrville, Ohio, USA, is the world's premier manufacturer of mobile telescoping masts, towers and pan and tilt positioners. We offer virtually every payload elevation and integration solution from the top brands; Will-Burt, GEROH, Integrated Tower Systems (ITS) and MAD – for defense, government, first responders, cellular, broadcast, energy production and other markets. Will-Burt also offers contract manufacturing, metal fabrication, powder-coating, and rapid prototyping services. All Will-Burt Company manufacturing locations are backed by a certified ISO 9001:2015 Quality Management System. Incorporated in 1918, Will-Burt is 100% employee-owned and is classified as a small business.



www.willburt.com

UNITED STATES WORLD HEADQUARTERS

401 Collins Blvd
Orrville, OH USA 44667
Telephone: 330.682.7015
Mast Customer Service: 330.684.4000
Fax: 330.684.1190
Email: info@willburt.com

INTEGRATED TOWER SYSTEMS

A WILL-BURT COMPANY

2703 Dawson Road, Tulsa, OK 74110
Telephone: 800.850.8535
Fax: 918.749.8537
Email: programs@itstowers.com

WILL-BURT EU

Unit 5b, Station Approach
Four Marks, Alton Hampshire,
GU34 5HN, United Kingdom
Telephone: +44 (0) 1403 265532
Fax: +44 (0) 1403 259072

WILL-BURT TURKEY

2118. Cad. No: 4, B101
Mustafa Kemal Mah. 06530 Çankaya
Ankara, Turkey
Telephone: +1 202 820 2184

EUROPE GEROH

A Will-Burt Company
Fischergasse 25
91344 Waischenfeld, Germany
Telephone: +49-9202-18-0
Fax: +49-9202-18-11
Email: info@geroh.com

ASIA SINGAPORE SALES OFFICE

1 Fullerton Road,
#02-01 One Fullerton,
Singapore 049213
Telephone: +65 6832 5689
Fax: +65 6722 0664