



①	SC SERIES 5TH WHEEL GOOSENECK TRAILER	⑨	15,000 LB STATIC CAPACITY LEVELING JACKS	⑰	PHOTOCELL LIGHTS	⑳	DIRECT DRIVE OPERATING TOWER SYSTEM	㉓	THERMOPLASTIC PVC ROOF SYSTEM
②	HYDRAULIC TOWER BASE STRUCTURE	⑩	SAE 2" KINGPIN TOWER COUPLER	⑱	STORAGE BOX	㉑	TOWER ELEVATED LOCK MECHANIZM	㉔	HD 6" SHELTER SKID W/ FORK POCKETS
③	106'/110' AGL TOWER SYSTEM	⑪	AIRBRAKE GLAD HANDS	⑲	OUTRIGGER JACK SAND/ MARSH PLATFORMS	㉒	TOWER TRANSPORT TIE DOWNS	㉕	3'x6' STEEL ENTRY DOOR W/ LEVER PASSAGE
④	16x8x9'-2" OD STEEL CLAD COMMUNICATIONS EQUIPMENT SHELTER	⑫	9'x8' GOOSENECK PLATFORM W/ STORAGE	⑳	STABILIZING OUTRIGGERS	㉓	SHELTER/ PLATFORM STEPS	㉖	12" STAINLESS STEEL GRAB HANDLE
⑤	36KW DIESEL GENERATOR	⑬	120V/60Hz TOWER CONTROL PANEL	㉑	SHELTER WIND STRAPS MAX 135 MPH	㉔	TOWER TOP ANTANNA MOUNTS	㉗	AUTO-LEVEL JACK TRANSFORMER/ POWER PANEL
⑥	±105-GALLON FUEL CELL	⑭	TANDEM 20,000 LB CAPACITY EACH AXLES	㉒	EXTERNAL LIGHTS	㉕	WAVE GUIDE ENTRY PORTS		
⑦	AUTOMATED ELEC. JACKS	⑮	GOODYEAR 215/75R LRH TIRES	㉓	STORAGE	㉔	24" GROUND BAR		
⑧	SHELTER LADDER	⑯	(2) 2.5 TON HVAC UNITS	㉔	SPARE TIRE ANDMOUNT	㉕	HUBBELL SHORE POWER CONNECTOR		

MATERIAL

THIS DRAWING IS THE PROPERTY OF INTEGRATED TOWER SYSTEMS. THE INFORMATION HEREIN SHALL NOT BE REPRODUCED OR TRANSFERRED IN ANY MANNER OR USED OR DISCLOSED TO OTHERS FOR ANY PURPOSES, EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY ITS.

INTEGRATED
ITS TOWER
SYSTEMS

ITS
 WWW.ITSTOWERS.COM
 918-749-8535

REMOVE BURRS & BREAK ALL SHARP EDGES, UNLESS OTHERWISE SPECIFIED DIMENSIONS IN INCHES.	DRAWN BY: JAB	TITLE: SC-16/48G-106
TOLERANCES: FABRICATION: ±1/16 MACHINING: ±1/64 FINISH: ±.005	CHECKED BY: CC	DRAWING # SC-16/48G-106
	APPROVED BY: CC	DATE 02/04/2011
		SCALE 1:96
		SHEET 1 OF 1