

MCU Mobile DVR 5318901

GOOD

MCU is a Hybrid H.264 MDVR that provides the perfect surveillance solution for vehicles or rugged environments. With a total of 4 cameras (4 Analog or 4 IP), the MCU is fully loaded with hardware and software characteristics to meet any market specification. The fully featured Mobile Witness Manager™ allows for live view, playback with Google Maps, and integration with Automatic Download, Health Monitor, and MobileLink™ software. All firmware and client software is developed, supported, and maintained in the USA for maximum network security, performance, and stability.



ESSENTIAL FEATURES

- Any Combination of 4 Cameras, Analog or Megapixel IP
- Dual Core ARM CPU Running Linux Embedded 3.0
- Analog Resolution: 960H, D1, HD1 and CIF
- H.264 Video Encoding
- Dual Streaming Video for Low-Bandwidth Applications
- Lockable, Removable Storage Tray
- 1 TB HDD
- Built-In Wi-Fi Module (802.11 N)
- Built-In 3-Axis Inertial Sensor
- Built-In GPS Module (patent pending route rebuild)
- Built-In Shock and Vibration Absorber
- PTZ Control
- DIN-Style Mount, Small Profile (7"x7"x2")
- Web-Based Client Software
- Integration with Microsoft Active Directory

OPTIONAL INTERFACES

- Bluetooth 4.0
- Battery Backup
- USB 3.0 Caddy for the Fastest Video File Access and Retrieval
- Tire Pressure Monitoring System
- OBDII/J1939 (CANBUS)
- Built-In GPRS/3G/Edge/CDMA/LTE Modules
- RFID Tag Reader
- MiFare Access Control Smart Card Reader
- Motorola MOTOTRBO Radio
- Mirror Recording Function for Fault Tolerance (Police Package)
- Radar Gun (Police Package)
- Unique Multi-Channel Audio Recording Matrix (Police Package)
- Video Classification (Police Package)

SOFTWARE SOLUTIONS

MOBILE WITNESS MANAGER

- Web client
- Playback video, audio, map, and associated metadata
- Allows remote MDVR configuration

FREE

AUTO DOWNLOAD SERVER

- Automatically downloads videos via Wi-Fi or USB
- Powerful search interface
- Creates a file database
- 100s of assets managed at one video storage server or multiple ADS locations
- Scheduled video downloads

LICENSED

MOBILELINK

- Monitor 1000s of assets on one server
- Allows automated alarm notification
- Geo-fence, route deviation alerts
- Route rebuild
- Mobile DVR health monitor

LICENSED



www.willburt.com
330-684-4000



SYSTEM	OS	Embedded Linux 3.0
	Operation Interface	Handheld IR remote controller or Control Panel Monitor
	Storage	Removable caddy with selectable interface: 1 TB HDD with 2.5" True SATA III HDD/SSD interface
	Mirror Recording (Raid 0)	SDXC 4~256GB option
	Signal System	NTSC/PAL
VIDEO	Analog Camera Input	Up to 4 cameras with DIN connector for easy deployment (A + V +Power on one industrial-grade connector)
	IP Camera Input	Up to 4 IP cameras (2.0 MP at 30 FPS). ONVIF 2.0 / RTSP
	Image Quality	Adjustable to 8 levels
	FWD/Playback Speed	x2, x4, x1/2, x1/4
	Stream Standard	ISO14496-10 H.264 Baseline/Main/High Profile Level 4.2
	Record Resolution	CIF, HD1, D1 and 960H (Analog), 8x's 2 MP @ 30 FPS (IP) or 8X's 5 MP @ 7 FPS (IP)
	Image Compression	H.264
	Global FPS (Analog)	NTSC 120 FPS @ D1 , 120 FPS @ 960H
	Display Resolution	704x576 for PAL @ D1 / 720x480 pixels for NTSC @ D1
AUDIO	Display	Up to 4 Images (4 Analog or 4 IP)
	Audio Input	8 Mono
	Audio Output	1 Mono
	Audio Compression	ADCPM+G.711 (8kbps) for better compatibility
I/O INTERFACE	Multi-Channel Audio	Feature Included on Police Package only
	Video Out	1x Composite output with RCA connector, 1x DIN connector with Audio +Video +Power on pigtail
	USB	USB 2.0 x1 on the front panel, x2 rear panel, x1 USB 3.0 on the HDD caddy
NETWORK	Serial	x2 RS-485, x2 RS-232
	Protocol	TCP-IP and UDP
	LAN	1 RJ45, 10/100 NIC
	Wireless Communications	Models 5318902 and 5318903
ALARM	WIFI	Built-in Wi-Fi module, IEEE 802.11 N
	Input	8 alarm inputs (5V~12V), for door, brakes, alarms, sensors, etc.
	Output	2 alarm outputs (12V), lights, audio alerts, etc.
	Software Multi-Mode	Video Loss, temperature, voltage, speed, motion, block camera, 3-axis accelerometer
POWER REQUIREMENTS	Ignition Detection	Detectable ignition power wire with programmable delay shutdown for auto-downloading
	Power Consumption	Average 10w with mechanical HDD, 55mA in standby mode
	Power input	8~36VDC, typical 12V DC @5A, 24V @ 3A
PHYSICAL DEMANDS	Height	50.67mm / 2"
	Width	177.99mm / 7"
	Depth	177.34mm / 7"
	Weight	1.2Kg / 3Lb
OTHER FUNCTIONS	Motion Detection	Yes, configure per-camera, 104 zone grid
	Block Camera Detection	Yes, configure per-camera with 4 sensitivity options
	Record Mode	Manual, Continuous, Timer, Alarm
	Time Clock	Perpetual built-in clock, customizable format
	Time Sync	GPS and NTP
	GPS Function	Built-in GPS module
	Data R/W Mode	FIFO
	3-Axial accelerometer	On board module (except in Lite version)
ENVIRONMENT	Operating Temperature	-40~85°C (achieved using industrial-grade storage media)
	Relative Humidity	5%~80%
	Vibration Resistance	<2 Grms

CONTACT YOUR SALES REPRESENTATIVE TODAY

The Will-Burt Company, headquartered in Orrville, Ohio, USA, is the world's premier manufacturer of mobile telescoping masts, towers and pan and tilt positioners. We offer virtually every payload elevation and integration solution from the top brands; Will-Burt, GEROH, Integrated Tower Systems (ITS) and MAD – for defense, government, first responders, cellular, broadcast, energy production and other markets. Will-Burt also offers contract manufacturing, metal fabrication, powder-coating, and rapid prototyping services. All Will-Burt Company manufacturing locations are backed by a certified ISO 9001:2015 Quality Management System. Incorporated in 1918, Will-Burt is 100% employee-owned and is classified as a small business.



www.willburt.com

UNITED STATES WORLD HEADQUARTERS

401 Collins Blvd
Orrville, OH USA 44667
Telephone: 330.682.7015
Mast Customer Service: 330.684.4000
Fax: 330.684.1190
Email: info@willburt.com

INTEGRATED TOWER SYSTEMS

A WILL-BURT COMPANY
2703 Dawson Road, Tulsa, OK 74110
Telephone: 800.850.8535
Fax: 918.749.8537
Email: programs@itstowers.com

WILL-BURT EU

Unit 5b, Station Approach
Four Marks, Alton Hampshire,
GU34 5HN, United Kingdom
Telephone: +44 (0) 1403 265532
Fax: +44 (0) 1403 259072

WILL-BURT TURKEY

2118. Cad. No: 4, B101
Mustafa Kemal Mah. 06530 Çankaya
Ankara, Turkey
Telephone: +1 202 820 2184

EUROPE GEROH

A Will-Burt Company
Fischergasse 25
91344 Waischenfeld, Germany
Telephone: +49-9202-18-0
Fax: +49-9202-18-11
Email: info@geroh.com

ASIA SINGAPORE SALES OFFICE

1 Fullerton Road,
#02-01 One Fullerton,
Singapore 049213
Telephone: +65 6832 5689
Fax: +65 6722 0664